


# Surveillance Storage Capacity Helping to Keep Us Safer 24/365

High capacity HDDs of up to 6TB designed for security camera systems that require continuous operation throughout the year. These HDDs can support as many as 64 high resolution cameras\*, and provide flexible capacity for future expansion of security camera systems.

\*Subject to model specification.

## Surveillance Hard Disk Drive



### Reliability and Durability

Designed for 24/365 operation and a million hour MTTF, this series provides the reliability to give you peace of mind, and also has the durability to operate in ambient temperatures ranging from 0 - 70 °C.

### Flexible Expandability

Can be support as many as 64 high resolution cameras\*, and help provide flexible capacity for future expansions, such as the addition of storage capacity in single or multiple drive bays.

### Multi-Capacity Lineup

Capacities in the lineup range from 1TB to 6TB, enabling you to choose the surveillance HDD options that best fit your needs.

## S300 Hard Disk Drive

### Application

- Surveillance Network Video Recorders (sNVR)
- Surveillance Digital Video Recorders (sDVR)
- Hybrid sDVR (Analog and IP)
- RAID Storage Arrays for Surveillance Solutions

### Specifications

	S300			
Formatted Capacity	6TB	4TB	2TB	
Model Number	HDWT860UZSVA (DT02ABA600VH)	HDWT840UZSVA (DT02ABA400VH)	HDWT720UZSVA (DT02ABA200V)	
<b>Specification</b>				
Recording Technology	SMR			
Interface	SATA 6 Gbit/s			
Form Factor	3.5-inch (Height: 26.1 mm, Length: 147.0mm, Wide: 101.85 mm)			
Maximum Weight	680 g	650 g	440 g	
<b>Performance</b>				
Rotation Speed	5400 rpm			
Number of Camera Supported	Up to 64		Up to 32	
Drive Bays Supported	Up to 8			
24/7 Operation	Supported			
Rotation Vibration (RV) Sensor	Supported			
Shock Sensor	Supported			
Buffer Size	256 MiB		128 MiB	
Maximum Data Transfer Speed (Sustained) (Typ.)	184 MB/s ( 176.4 MiB/s)			
<b>Reliability</b>				
MTTF	1,000,000 hours			
Load/Unload cycles	600 000 times			
Workload Rating	180 TB Transferred per year			
<b>Power Requirements</b>				
Supply Voltage	5 V DC ±5%   12 V DC ±10%			
Consumption	Active	Idle		
		2.81 W	2.33 W   2.08 W	
<b>Environmental Requirements</b>				
Temperature	Operating	0 to 70 °C (Surface)		
	Non-Operating	-40 to 70 °C		
Vibration	Non-Operating	29.4 m/s <sup>2</sup> { 3.0 G } (5 to 500 Hz)		
Shock	Non-Operating	2940 m/s <sup>2</sup> { 300 G } (2 ms duration)	3430 m/s <sup>2</sup> { 350 G } (2 ms duration)	
Acoustic	Idle	24 dB	22 dB	21 dB

Limited Warranty: 3 years

Definition of capacity: Toshiba defines a gigabyte (GB) as 1,000,000,000 bytes and a terabyte (TB) as 1,000,000,000,000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2<sup>30</sup> = 1,073,741,824 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may vary. [A mebibyte (MiB) means 2<sup>20</sup>, or 1,048,576 bytes. [MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF. [Read and write speed may vary depending on the host device, read and write conditions, and file size. [“3.5-inch” means the form factor of HDDs. They do not indicate drive’s physical size. [Workload is a measure of the data throughput of the year, and it is defined as the amount of data written, read or verified by commands from the host system. [Operation of the drive when it has a high surface temperature will shorten its useful life. The recommended operating condition is with a surface temperature of less than 60°C. [Number of surveillance cameras support capability is defined by performance simulation with High Definition cameras at 10Mbit/s rate. Actual results may vary based on various factors, including the types of cameras installed, the system’s hardware and software capabilities, and the video compression technology used, as well as system variables such as resolution, frames per second, and other settings. [Before creating and producing designs and using, customers must also refer to and comply with the latest versions of all relevant information of this document and the instructions for the application that Product will be used with or for. Product images used do not represent actual products.

## Toshiba Electronics Asia (Singapore) Pte Ltd

www.toshiba-storage.asia

