

S300 SURVEILLANCE Hard Drives

[DT02-V Series]

Toshiba's S300 Surveillance Series are designed for purpose-built consumer and commercial surveillance video systems supporting up to 32 cameras^[1]. The versatile capacity allows solutions designers to customize the storage capacity that best aligns with image resolution and data retention period



Product image used do not represent actual product.

KEY FEATURES

- Up to 6TB^[2] capacity
- Supports up to 32 cameras high-definition streams
- 128 MiB Cache buffer helps to smooth video recording and guard against frame drops
- Designed for 24/7 operation
- Annual workload rating of 180 TB/year^[3]
- MTTF of 1M hours^[4]
- Industry-standard 3.5-inch form-factor^[5] and SATA interface
- Advanced Format 512e Sector Technology
- Drive-Managed SMR (Shingled Magnetic Recording) Technology

APPLICATIONS

- Network Video Recorders (NVR)
- Entry- and Mid-Range Surveillance NVR (SNVR) and SDVR Platforms
- Hybrid (analog and IP) SDVR Platforms

SPECIFICATIONS

Item		HDWT760UZSVA [DT02ABA600V]	HDWT740UZSVA [DT02ABA400V]	HDWT720UZSVA [DT02ABA200V]
Interface		SATA-3.3		
Formatted Capacity		6 TB	4 TB	2 TB
Performance	Interface Speed ^[6]	6.0 Gbit/s, 3.0 Gbit/s, 1.5 Gbit/s		
	Rotation Speed	5400 rpm		
	Buffer Size	128 MiB ^[7]		
	Maximum Data Transfer Speed ^[8] (Sustained) (Typ.)	176.4 MiB/s		
Logical Data Block Length ^[9]		HOST: 512 B, DISK: 4096 B		
Supply Voltage	Allowable Voltage	12 V ^[10] ± 10 % / 5 V ^[10] ± 5 % ^[11]		
Power Consumption	Operating (Typ.) ^[12]	4.48 W	4.11 W	4.01 W
	Active idle (Typ.)	2.69 W	2.36 W	2.08 W
	Standby (Typ.)	0.20 W	0.20 W	0.31 W
Acoustics (Sound Power) ^[13]	Low Power Idle (Typ.)	24 dB	22 dB	21 dB

ENVIRONMENTAL LIMITS

Item		Specification	
Ambient Temperature	Operating	0 °C to 60 °C (No condensation)	
	Non-Operating ^[14] [15]	- 40 °C to 70 °C (No condensation)	
Relative Humidity	Operating	5 % to 90 % R.H. (No condensation)	
	Non-Operating	5 % to 95 % R.H. (No condensation)	
Altitude	Operating	- 305 m to 3048 m	
	Non-Operating ^[14]	- 305 m to 12 192 m	
Shock ^[14]	Operating	686 m/s ² { 70 G } (2 ms duration)	
	Non-Operating	2940 m/s ² { 300 G } (2 ms duration)	3430 m/s ² { 350 G } (2 ms duration)
Vibration ^[14]	Operating ^[15]	4.90 m/s ² { 0.50 G } (5 to 350 Hz) 2.45 m/s ² { 0.25 G } (350 to 500 Hz)	
	Non-Operating ^[16]	29.4 m/s ² { 3.0 G } (5 to 500 Hz)	

RELIABILITY

Item	Specification
MTTF	1 000 000 hours
Non-Recoverable Error Rate	1 error per 10 ¹⁴ bits read
Load / Unload	600 000 times
Availability	24 hours/day, 7 days/week
Rated Annual Workload (Total TB Transferred per Year, R/W)	180 TB/year

MECHANICAL SPECIFICATIONS

Item	HDWT760UZSVA [DT02ABA600V]	HDWT740UZSVA [DT02ABA400V]	HDWT720UZSVA [DT02ABA200V]
Width	101.6 mm ± 0.25 mm		
Height (Max)	26.1 mm		
Length (Max)	147.0 mm		
Weight (Max)	680 g	650 g	440 g

[1] Number of surveillance cameras support capability is defined by performance simulation with High Definition cameras at 4Mbit/s rate. Actual results may vary based on various factors, including the types of cameras installed, the system's hardware and software capabilities, and the video compression technology used, as well as system variables such as resolution, frames per second, and other settings. [2] Definition of capacity: Toshiba defines a megabyte (MB) as 1 000 000 bytes, a gigabyte (GB) as 1 000 000 000 bytes and a terabyte (TB) as 1 000 000 000 000 bytes. A computer operating system, however, reports storage capacity using powers of 2 for the definition of 1GB = 2³⁰ = 1 073 741 824 bytes and therefore shows less storage capacity. Available storage capacity (including examples of various media files) will vary based on file size, formatting, settings, software and operating system, such as Microsoft Operating System and/or pre-installed software applications, or media content. Actual formatted capacity may vary. [3] Workload is defined as the amount of data written, read or verified by commands from host system. [4] MTTF (Mean Time to Failure) is not a guarantee or estimate of product life; it is a statistical value related to mean failure rates for a large number of products which may not accurately reflect actual operation. Actual operating life of the product may be different from the MTTF. [5] "3.5-inch" means the form factor of HDDs. They do not indicate drive's physical size. [6] Read and write speed may vary depending on the host device, read and write conditions, and file size. [7] A kibibyte (KiB) means 2¹⁰, or 1024 bytes, a mebibyte (MiB) means 2²⁰, or 1 048 576 bytes, and a gibibyte (GiB) means 2³⁰, or 1 073 741 824 bytes. [8] The maximum sustained data rate and interface speed may be restricted to the response speed of host system and by transmission characteristics. 1 Gbit/s = 1 000 000 000 bit/s. 1 MiB/s = 1 048 576 B/s. [9] Read-modify-write is supported. [10] Input voltages are specified at the HDD connector side, during HDD ready state. [11] Make sure the value is not less than DC -0.3 V (less than -0.6 V, 0.1 ms) when turning on or off the power. [12] Operating watt is measured using 80% random read/write and 20 % performance idle. [13] The measuring method is based on ISO 7779. [14] Vibration applied to the HDD is measured at near the mounting screw hole on the frame as much as possible. [15] At random seek write/read and default on retry setting with log sweep vibration. [16] At power-off state after installation

*Before creating and producing designs and using, customers must also refer to and comply with the latest versions of all relevant information of this document and the instructions for the application that Product will be used with or for.

*Company names, product names, and service names may be trademarks of their respective companies.